



INSTALLING INSTRUCTIONS


Pag. 1/4

ALL OPERATIONS MUST BE CARRIED OUT BY QUALIFIED PERSON




1) Rimuovere le viti e aprire la lampada.

Remove the screws and open the lamp.



2) Scollegare il connettore.

Disconnect the connector.



USE A SOFT DAMP CLOTH TO CLEAN ALL LAMP PARTS

ALL OPERATIONS MUST BE CARRIED OUT BY QUALIFIED PERSON

JOLLY US 32 - 1...10 V & PUSH



Direct current dimmable electronic drivers with DIP-SWITCH
Alimentatori elettronici regolabili in corrente continua con DIP-SWITCH

Made in Italy



0/1...10 V

PUSH

constant
CURRENTconstant
VOLTAGE

IS 15885
(Part 2 / Sec 13)

 R - 41049751

DAMP
LOCATION

UL-CLASS2 (4)

 CSA-LVLE

EN 05

KEMA
EUR

(5)

(6)
 PENDING

110

M

M



EL SELV 60V



DC JOLLY US

3KV DIFF.
4KV COMM.

ACTIVE
PFC

DIP-SWITCH

SYNC.

SAFETY
PROTECTIONS





IP 20

SCREW
FIXING


Ø72
2,83"

Weight - Peso gr. 120 / 4,2 oz.
 Pcs - Pezzi 50

Compatible with ZHAGA (AS1)





PUSH diagram - Collegamento PUSH



1...10 V diagram - Collegamento 1...10 V

USE A SOFT DAMP CLOTH TO CLEAN ALL LAMP PARTS




3) Fissare la placca metallica alla parete. (Usare i tasselli forniti).
Assicurarsi che la scritta "UP" sia rivolta verso l'alto.

Fix the metal plate to the wall. (Use anchors provided).
Make sure that the word "UP" is facing upwards.

4) Collegare i cavi (4A) e collegare il connettore (4B).

Connect the wires (4A) and connect the connector (4B).




5) Avvitare nuovamente le viti alla lampada.

Screw the screws back onto the lamp



6) Agganciare il paralume al gancio della struttura.

Hook the lampshade to the hook of the structure .



7) Posizionare il paralume tirandolo verso il basso, agganciarlo ai due ganci inferiori.

Position the shade pulling downwards, hooking it to the two lower hooks.